



WET CHEMICAL, FOAM, WATER AND STAINLESS STEEL FIRE EXTINGUISHERS

Product Code	Component
A018	6 Litre (Class F) Wet Chemical Type Fire Extinguisher
Description	Specifications
Charge	6L
Fire Extinguisher Complete Full Weight	11.4Kg
Fire Extinguisher Complete Empty Weight	5.4Kg
Cylinder Empty Weight	3.1Kg
Cylinder Length (mm)	430±2
Out-cylinder diameter (mm)	162
Volume (L)	7.5
Min. Wall Thickness of Cylinder mm)	1.24
Material	ST13
Discharge Time	>9 sec.
Range of Discharge	3m
Corrosion Protection	LJ766 powder inner coating
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Fire Rating	13A 75F
Working Temperature	0°C ~ +60°C
Packing Size (cm)	17.5 x 17 x 55



Product Code	Component
G007	2.0 Litre 3% AFFF Type, Mild Steel Fire Extinguisher
Description	Specifications
Charge	3L
Fire Extinguisher Complete Full Weight	3.9Kg
Fire Extinguisher Complete Empty Weight	1.9Kg
Cylinder Empty Weight	1.1Kg
Cylinder Length (mm)	317±2
Out-cylinder diameter (mm)	110
Volume (L)	2.5
Min. Wall Thickness of Cylinder mm)	1.24
Material	ST13
Discharge Time	>6 sec.
Range of Discharge	2m
Corrosion Protection	LJ766 powder inner coating
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Working Temperature	0°C ~ +60°C
Packing Size (cm)	13.5 x 12.5 x 42





Product Code	Component
G006	9 Litre 3% AFFF Type, Mild Steel Fire Extinguisher
Description	Specifications
Charge	9L
Fire Extinguisher Complete Full Weight	13.8Kg
Fire Extinguisher Complete Empty Weight	4.8Kg
Cylinder Empty Weight	4.65Kg
Cylinder Length (mm)	519±2
Out-cylinder diameter (mm)	184
Volume (L)	12
Min. Wall Thickness of Cylinder mm)	>1.32
Material	ST13
Discharge Time	>12 sec.
Range of Discharge	3-8m
Corrosion Protection	LJ766 powder inner coating
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Fire Rating	13A 183B
Working Temperature	0°C ~ +60°C
Packing Size (cm)	19.5 x 20 x 64



Product Code	Component
G009	9 Litre Water Type, Mild Steel Fire Extinguisher
Description	Specifications
Charge	9L
Fire Extinguisher Complete Full Weight	13.8Kg
Fire Extinguisher Complete Empty Weight	4.8Kg
Cylinder Empty Weight	4.65Kg
Cylinder Length (mm)	519±2
Out-cylinder diameter (mm)	184
Volume (L)	12
Min. Wall Thickness of Cylinder mm)	>1.32
Material	ST13
Discharge Time	>12 sec.
Range of Discharge	3-8m
Corrosion Protection	LJ766 powder inner coating
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Fire Rating	13A
Working Temperature	0°C ~ +60°C
Packing Size (cm)	19.5 x 20 x 64





Product Code	Component
G002	9 Litre 3% Type, Stainless Steel Fire Extinguisher
Description	Specifications
Charge	9L
Fire Extinguisher Complete Full Weight	12.3Kg
Fire Extinguisher Complete Empty Weight	3.3Kg
Cylinder Empty Weight	2.65Kg
Cylinder Length (mm)	560
Out-cylinder diameter (mm)	162
Volume (L)	10.5
Min. Wall Thickness of Cylinder mm)	1.2
Material	SUS304
Discharge Time	>12 sec.
Range of Discharge	3-8m
Corrosion Protection	Stainless Steel (SUS404)
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Fire Rating	13A 183B
Working Temperature	0°C ~ +60°C
Packing Size (cm)	18.5 x 18.5 x 66.5



Product Code	Component
A016	9Kg Dry Chemical Powder Type, Stainless Steel Fire Extinguisher
Description	Specifications
Charge	9Kg
Fire Extinguisher Complete Full Weight	12.3Kg
Fire Extinguisher Complete Empty Weight	3.3Kg
Cylinder Empty Weight	2.65Kg
Cylinder Length (mm)	560
Out-cylinder diameter (mm)	162
Volume (L)	10.5
Min. Wall Thickness of Cylinder mm)	1.2
Material	SUS304
Discharge Time	>12 sec.
Range of Discharge	8m
Corrosion Protection	Stainless Steel (SUS404)
Working Pressure	1400kPa
Hydrostatic Test Pressure	2100kPa
Bursting Pressure of Cylinder	>5500kPa
Safety Device	2100 ~ 2600kPa
Size / Type of Pressure Gauge Fitted	1/8" NPT / Bourdon Tube
Fire Rating	27A 144B
Working Temperature	-30°C ~ +60°C
Packing Size (cm)	18.5 x 18.5 x 66.5

